ART.NUMBER DETAILS

C001086 PROFI 12.0M DV H

Vredo Profi 12m DV H

Machinenumber: 1025.012Year of construction 2022

Specifications:

- Working width 12 meter
- Inter row distance 18,75 cm
- Vredo double V-disc system (spoke discs)
- 64 pairs of discs
- Mechanic and suspended duo disc elements, free of maintenance
- Duo disc elements are mounted with torsion rubbers to be able to rotate/steer in a small angle
- Casette seals and double row ball bearings for disc bearings
- Easy to replace wear parts: discs, scraper blocks and steel turf guards
- · Hydraulic dropstop
- Open constructed folding frame made out of 5 parts
- Automatic (hydraulic and mechanic) transport safety
- Automatic mechanic operated reflecting disc cover set for safe transport on the road
- 1 connection for central greasing of hinge points
- Frame has the possibility to lever in a free way thanks to the fact the hydraulic cylinders of in- and out folding are connected with each other by help of a parallelogram construction
- Parallelogram lever construction is locked in case hydraulic function of folding in is operated (adjustable for headland management)
- Leveling and unlevelling by way of adjusting the length of a special bar in the parallelogram construction
- Meets the requirements of the road transport legislation fort he Netherlands and Germany
- · Rear marking
- Registration plate holder incl. lightning
- 2x Vogelsang ExaCut ECQ 36-40 vertical distributor
- Slurry hoses 40mm, for precise distribution
- Stainless steel hose clamps on slurry hoses and rubber slurry outlets
- Transport width bottom: 2,98 m
- Transport width top: 2,48 m
- Height standing on the bottom: 3,80 m
- Weight ca. 3610kg
- LED lightning
- Demountable counterpart of A-frame`

Required connections:

- 2x 1/2" In/out folding (open center)
- 2x 1/2" dropstop (closed center)
- 2x 3/4" distributor (open center), distributor needs a continuous oil flow of 30L/min
- 1x 1/2" pressureless return line
- 6" KKV slurry hose connection on T-piece to distributors
- 1x connection for central greasing supplied by vehicle





Welysestraat 25a, 6669 DJ Dodewaard, Nederland Tel. +31 (0) 488 411254 | Fax. +31 (0) 488 412471 e-mail:info@vredo.com | www.vredo.com

IBAN: NL65INGB0007457180 BIC: INGBNL2A K.v.K. Tiel nr.: 11014234

BTW: NL 005054746B01



