

**ART.NUMBER****DETAILS**

G00100983

ZB3 8046

Vredo ZB3 8046

- Machinenummer: 1121.279
- Year of construction 2016
- Supportwheels

Specifications:

- Working width 8 meter
- Inter row distance 17.5 cm
- Vredo double disc system (spoke discs)
- SKF Central bearing lubrication and lubrication of other hinge points by automatic grease device fitted on slurry injector.
- Lubrication reservoir 4L
- Needed for power supply: 1 electrical connection point 12V 15A on vehicle
- Automatically hydraulic shutter set of the slurry outlets
- Horizontal Vogelsang Dosimat 50 distributor
- 3 sections-frame with automatic locking for safe road transport
- Device for positioning distributor in horizontal position
- Easy to replace wear-resistant HPME slide blocks
- Stainless steel hose clips on the slurry hoses and the rubber slurry outlets
- Transportation width 2,85 meter
- Weight  $\pm$ 3025kg
- Automatic reflecting disc cover for safe transport
- LED lightning kit
- A-frame quick connection
- Special angular-contact bearings as disc bearings
- 6" KKV (Male) Slurry hose connection on top of distributor

Required hydraulics:

- 3x Double acting (2x open center, 1x closed center), The distributor needs a continuous oil flow of 55L/min
- 1x pressure less return line

Connections:


- 2x 1/2" In/out folding
- 2x 1/2" closing rubber drop stop outlets
- 2x 3/4" distributor
- 1x 1/2" pressure less return line

**Vredo Dodewaard B.V.**

Welysestraat 25a, 6669 DJ Dodewaard, Nederland  
Tel. +31 (0) 488 411254 | Fax. +31 (0) 488 412471  
e-mail:info@vredo.com | www.vredo.com

IBAN: NL65INGB0007457180  
BIC: INGBNL2A  
K.v.K. Tiel nr.: 11014234  
BTW: NL 005054746B01

The fieldcare company



**Vredo Dodewaard B.V.**  
Welysestraat 25a, 6669 DJ Dodewaard, Nederland  
Tel. +31 (0) 488 411254 | Fax. +31 (0) 488 412471  
e-mail: info@vredo.com | www.vredo.com

IBAN: NL65INGB0007457180  
BIC: INGBNL2A  
K.v.K. Tiel nr.: 11014234  
BTW: NL 005054746B01



The fieldcare company