

ART.NUMBER**DETAILS**

G00100995

VT4546

Vredo VT4546

- Machinenummer: 0119.039
- Year of construction: 2016
- Hours: ± 9.810
- Dutch homologation
- Tirepressure inflation system

Specifications:

- Motor Deutz 330 kW / 450 PS water cooled TIER IIIB, Ad Blue
- Powered mechanic-hydraulically stepless 0 - 40 km/h at 1,500 engine rpm, automatically controlled
- Fuel tank approx. 450 liters
- Ad Blue Tank 80 liters
- Suspended SuperComfort Claas-Vredo cabin, incl. fully automatic air conditioning and radio / CD player
- Operations console fitted to seat incl. joy-stick and touch-screen controller
- Air suspended super comfort seat
- Drivers instructor seat
- Electrically adjustable and heated mirrors incl. blind angle mirror
- 2 rotating beacons on cabin
- Front and back axle are fitted with a mechanical differential lock
- Rear axle constant drive, front-axle shiftable from cab (4 wheel drive)
- Two speed ranges, fieldrange 0-20kmh, roadrange 0-40kmh
- Steering 2 wheel, 4-wheel and crab steering. Crabsteer engagement with footswitch
- Suspended front axle with level control, oscillation cushion and spring blocking
- 3 Double working valves at rear
- Equipped with free return line
- 3-point double working proportionally regulated rear linkage, torsion suspended and fitted with applicator suspension. Actively controlled: following, suspended or pressure releasing from cabin
- Control for rear linkage with remote control
- Automatic central lubrication system for basic vehicle with 4L can
- 1 closed system pump max 210 l/min, 400 bar
- 2 LS-pumps, 160 l/min, for steering
- 3 Double and single acting valves rear
- Reversing alarm
- Camera-monitor installation with LCD colour screen
- Equipped with cruise control
- 2 LED working light behind cab
- 4 Xenon working lights in cab roof

Pre-installation for the 19500V:

- Discharge data storable via USB
- Hydraulic connections for PF 9010
- Intake and discharge pipes under cab
- Connections for slurry distributor, power socket ZB, hitch suspension/damping via accumulator
- Telescopic cilinder for tipping slurrytank

The tank is equipped with the following as standard:

- Complete fibreglass construction on steel frame with twist-locks
- Light weight
- Tank volume 19,5 m3
- Tank is easy to clean due to the uniformity of its shape
- Tank is easy to remove
- Airing with overpressure protection
- Pump automatically switches off when full
- Tank can be hydraulically lifted for maintenance
- Not suitable for weighing system
- 2x LED working lights on backside of tank
- Extra big mudflaps

Specifications:

- Vogelsang displacement pump/VX186-390QD 9000 l/min with spiral plungers
- reverse option on slurry pump with touchscreen

Vredo Dodewaard B.V.

Welysestraat 25a, 6669 DJ Dodewaard, Nederland
Tel. +31 (0) 488 411254 | Fax. +31 (0) 488 412471
e-mail:info@vredo.com | www.vredo.com

IBAN: NL65INGB0007457180
BIC: INGBNL2A
K.v.K. Tiel nr.: 11014234
BTW: NL 005054746B01

The logo for Vredo, featuring the word "Vredo" in a stylized, red, cursive font.

The fieldcare company

- filling at reduced rpm (1,200)
- cutting filter VREDO FT5200 with dirt ejector, opened and emptied from cabin
- suction arm 8", can be swivelled 160°, together with 9000 l/min Vogelsang slurry pump and FT5200 cutting filter on separate removable front unit.
- 180° swivelling front-suction connection 6"
- electric/hydraulic operating
- dosing independent of driving speed and slurry distribution can be set (e.g. unloading when standing still)
- pre-settable injectors
- Equipped with extra step on bumper
- Standard equipped with extra working light on loading arm

TIRE PRESSURE-REGULATION SYSTEM VT

- Tire pressure regulation system with 4 Cylinder Compressor, including control from cabin on touchscreen terminal, 2 pre programmed

